THE ULTIMATE X-RAY SOLUTION



SAFETY INTERLOCK KIT Connect Your Safety System Easily





FOR MORE INFORMATION, VISIT OUR WEBSITE

Connect your safety system easily

EASY CONNECTION

The Safety Interlock systems (SIK) allows the connection of multiple safety systems simultaneously to the CP120B/ CP160B generators.

The SIK and CP Battery generator are both powered by one and the same CP Battery pack, allowing outdoor field usage, but can also be connected to the mains power supply (optional) if required.

SAFETY INTERLOCK KIT

3 meters + XLR 5 pin M Cable reel 20 meters (6 wires - straight)

Cable (TX/RX crossed) 1,5 meter with HRS 6 pins M 1,5 meter + HRS 3 pins M

D38999/26ZA35SN plug

The Safety Interlock Kit includes:

- 1x Safety Interlock Box
- 1x Flashing light
- 1x Door lock connector (incl. connector)
- 1x 20m connection cable on a reel to link the CP Battery generator
- 1x Trigger to operate the generator
- 1x CPB battery pack
- 1x CPB battery charger

FEATURES	Unit	SAFETY INTERLOCK KIT
Operating temperature	°C/F°	0 to 50 / 32 to 122
Storage temperature	°C/F°	-20 to 70 / -4 to 158
Input voltage	Vdc	37 (Li-Ion battery)
Nominal power consumption	W	6(about 5 hours of continuous work)
Door control		Included



CONNECTORS TO THE SIK	SAFETY INTERLOCK KIT
XLR 5 pins F	to the interlock box
HRS 6 pins F	to the X-ray generator
DB9 M	to the battery
HRS 3 pins F	to manual trigger
Door control	D389996 pin
Safety key switch	



FOR MORE INFO, VISIT OUR WEBSITE

All specifications are non contractual and subject to change without prior notice.

TELEDYNE ICM

CABLES

Manual trigger Door control cable

Warning light system

Safety interlock box to X-ray generator

Zoning Les Plenesses / Rue Du Progrès 3 / B-4821 Andrimont (Dison) - Belgium +32 (0)87 44 01 50 / icm.sales@teledyne.com

Part of the Teledyne Imaging Group

Everywhere**you**look[™]

TELEDYNE ICM